

Link do produktu: <https://www.gtautomation.pl/czujnik-indukcyjny-m12-nbb2-12gm50-a2-v1-326161-0029-pepperfuchs-zasięg-działania-sn2-mm-złącze-gwintowane-m12-x-1-p-5080.html>



Czujnik Indukcyjny M12 NBB2-12GM50-A2-V1 326161-0029 Pepperl+Fuchs, Zasięg działania sn=2 mm, Złącze Gwintowane M12 x 1

Cena brutto	250,00 zł
Cena netto	203,25 zł
Dostępność	Dostępny
Czas wysyłki	na zapytanie
Numer katalogowy	087764
Producent	PEPPERL+FUCHS

Opis produktu

General specifications
Switching function
Output type
Rated operating distance
Installation
Output polarity
Assured operating distance

Normally open (NO)
PNP
2 mm
flush
DC
0 ... 1.62 mm (-25 ... 70 °C (-13 ... 158 °F))
0 ... 1.52 mm (-40 ... -25 °C (-40 ... -13 °F))
0.3
0.2
0.7

Reduction factor r_{Al}
Reduction factor r_{Cu}
Reduction factor r_{304}
Nominal ratings
Operating voltage
Switching frequency
Reverse polarity protection
Short-circuit protection
Voltage drop
Operating current
Off-state current
No-load supply current
Switching state indicator
Functional safety related parameters
MTTF_d
Mission Time (T_M)
Diagnostic Coverage (DC)
Approvals and certificates
EAC conformity
UL approval
CSA approval
CCC approval

10 ... 30 V
0 ... 1500 Hz
reverse polarity protected
pulsing
≤ 3 V
0 ... 200 mA
0 ... 0.5 mA typ. 0.1 µA at 25 °C
≤ 17 mA
Multihole-LED, yellow

1060 a
20 a
0 %

TR CU 020/2011
cULus Listed, General Purpose
cCSAus Listed, General Purpose
CCC approval / marking not required for
products rated ≤36 V

Ambient conditions
Ambient temperature

-40 ... 70 °C (-40 ... 158 °F)

Mechanical specifications

Connection type

Housing material

Sensing face

Housing diameter

Degree of protection

Connector M12 x 1 , 4-pin

brass, nickel-plated

PBT

12 mm

IP67