

Link do produktu: <https://www.gtautomation.pl/v1-w-5m-pur-p-5102.html>

V1-W-5M-PUR



Cena brutto	52,58 zł
Cena netto	42,75 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Producent	PEPPERL+FUCHS

Opis produktu

Opis produktu		
Female cordset, M12, 4-pin, PUR cable		
General specifications		
Number of pins		4
Connection 1		socket
Construction type 1		right angle
Threading 1		M12
Connection 2		cable end
Electrical specifications		
Operating voltage		max. 250 V AC/DC
Operating current		max. 4 A
Compliance with standards and directives		
Standard conformity	Degree of protection	EN 60529:2000
	Standards	IEC 61076-2-101:2008
	Flammability	Grip: UL 94
Ambient conditions		
Ambient temperature		Body: -40 ... 90 °C (-40 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -25 ... 80 °C (-13 ... 176 °F)
Pollution degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		1 mm
Degree of protection		IP67 / IP68 / IP69k
Material	Contacts	CuSn / Au
	Contact surface	Au
	Body	TPU, black
	Cable	PUR
	Slotted nut	Diecast zinc
	Core insulation	PP
Cable		fine-strand, flexible
	Sheath diameter	Ø 4.8 mm
	Bending radius	> 10 x cable diameter, moving > 8 x cable diameter, fixed
	Color	grey
	Cores	4 x 0.34 mm ²
	Conductor construction	19 x 0.15 mm Ø
	Length	5 m
Flammability	Contact carrier	94 HB
	Housing	94 V-2