

Link do produktu: <https://www.gtautomation.pl/v11-g-5m-pur-p-5096.html>



V11-G-5M-PUR

Cena brutto	47,05 zł
Cena netto	38,25 zł
Dostępność	Dostępność - 3 dni
Czas wysyłki	24 godziny
Producent	PEPPERL+FUCHS

Opis produktu

Female cordset, M12, 3-pin, PUR cable

General specifications

Number of pins

Connection 1

Construction type 1

Threading 1

Connection 2

Electrical specifications

Operating voltage

Test voltage

Operating current

Volume resistance

Ambient conditions

Ambient temperature

Pollution degree

Mechanical specifications

Contact elements

Pin diameter

Degree of protection

Material

Cable

Contacts

Contact surface

Body

Cable

Slotted nut

Core insulation

Sheath diameter

Bending radius

Color

Cores

Conductor construction

Length

3

socket

straight

M12

cable end

max. 250 V AC/DC

> 1500 V_{eff} AC

max. 4 A

< 5 mΩ

-25 ... 100 °C (-13 ... 212 °F)

For temperatures over 80 °C (176 °F)

reduced elongation at rupture

3

spring-loaded contact socket

1 mm

IP67 / IP68 / IP69k

CuSn / Au

Au

TPU, green

PUR

Diecast zinc

PP

fine-strand, flexible

Ø 4.8 mm

> 10 x cable diameter, moving

grey

3 x 0.34 mm²

19 x 0.15 mm Ø

5 m