

Link do produktu: <https://www.gtautomation.pl/v11-w-5m-pur-p-5094.html>



V11-W-5M-PUR

Cena brutto	47,05 zł
Cena netto	38,25 zł
Dostępność	Dostępność - 3 dni
Czas wysyłki	24 godziny
Producent	PEPPERL+FUCHS

Opis produktu

Product Description

Female cordset, M12, 3-pin, PUR cable

General specifications

Number of pins

3

Connection 1

socket

Construction type 1

right angle

Threading 1

M12

Connection 2

cable end

Electrical specifications

Operating voltage

max. 250 V AC/DC

Operating current

max. 4 A

Compliance with standards and directives

Standard conformity

Degree of protection

EN 60529:2000

Standards

IEC 61076-2-101:2008

Flammability

Grip: UL 94

Ambient conditions

Ambient temperature

-25 ... 100 °C (-13 ... 212 °F)

For temperatures over 80 °C (176 °F)

reduced elongation at rupture

3

Pollution degree

Mechanical specifications

Contact elements

spring-loaded contact socket

Pin diameter

1 mm

Degree of protection

IP67 / IP68 / IP69k

Material

Contacts

CuSn / Au

Contact surface

Au

Body

TPU, black

Cable

PUR

Slotted nut

Diecast zinc

Core insulation

PP

Cable

fine-strand, flexible

Sheath diameter

Ø 4.8 mm

Bending radius

> 10 x cable diameter, moving

Color

grey

Cores

3 x 0.34 mm²

Conductor construction

19 x 0.15 mm Ø

Length

5 m

Flammability

Contact carrier

94 HB

Housing

94 V-2