

Link do produktu: <https://www.gtautomation.pl/v3-gm-10m-pur-p-5097.html>



V3-GM-10M-PUR

Cena brutto	59,96 zł
Cena netto	48,75 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Producent	PEPPERL+FUCHS

Opis produktu

Opis produktu

Female cordset single-ended, M8, 3-pin, PUR cable

General specifications

Number of pins

3

Connection 1

socket

Construction type 1

straight

Threading 1

M8

Connection 2

cable end

Electrical specifications

Operating voltage

max. 48 V AC / 60 V DC

Operating current

max. 3 A

Volume resistance

< 5 mΩ

Compliance with standards and directives

Standard conformity

Specification

connector M8 x 1 : IEC 61076-2-104

Ambient conditions

Ambient temperature

-40 ... 90 °C (-40 ... 194 °F)

cable, fixed: -40 ... 80 °C (-40 ... 176 °F)

cable, flexing: -20 ... 80 °C (-4 ... 176 °F)

3

Pollution degree

Mechanical specifications

Contact elements

Pin diameter

Degree of protection

Material

spring-loaded contact socket

1 mm

IP67

Cable

Contacts

CuSn / Au

Contact surface

Au

Body

TPU, black

Cable

PUR

Slotted nut

Diecast zinc

Core insulation

PP

Sheath diameter

fine-strand, flexible

Bending radius

Ø 4.3 mm

> 15 x cable diameter, moving

> 8 x cable diameter, fixed

Color

grey

Cores

3 x 0.25 mm²

Conductor construction

14 x 0.15 mm Ø

Length

10 m

Flammability

Contact carrier

94 HB

Housing

94 V-2