

Link do produktu: <https://www.gtautomation.pl/v31-gmv4a-5m-pp-w1-p-5083.html>



V31-GMV4A-5M-PP-W1

Cena brutto	71,96 zł
Cena netto	58,50 zł
Dostępność	Dostępność - 3 dni
Czas wysyłki	24 godziny
Producent	PEPPERL+FUCHS

Opis produktu

Opis produktu	Single-ended female cordset, M8, V4A stainless steel, wash-down design, 4-pin, PP cable
General specifications	
Number of pins	4
Connection 1	socket
Construction type 1	straight
Threading 1	M8
Connection 2	cable end
Electrical specifications	
Operating voltage	max. 250 V AC/DC
Operating current	max. 4 A
Compliance with standards and directives	
Standard conformity	
	Degree of protection
	Standards
	Halogen-free
	Temperature resistance
	Material
Ambient conditions	EN 60529
Ambient temperature	IEC 61076-2-101
	IEC 60754-1
	DIN EN 60811-1-4
	FDA-compliant in accordance with FDA 21 CFR 177.2600
	cable, flexing: -25 ... 105 °C (-13 ... 221 °F)
	cable, fixed: -40 ... 105 °C (-40 ... 221 °F)
	3
Pollution degree	
Mechanical specifications	
Contact elements	spring-loaded contact socket
Degree of protection	IP67 / IP68 / IP69
Material	
	Contacts
	Contact surface
	Body
	Cable
	Slotted nut
	Seal
	Core insulation
	Temperature resistance
Cable	
	Sheath diameter
	Bending radius
	Color
	Number of cores
	Core cross-section
	Conductor construction

Drag chain suitability	Length	5 m
	Drag chain cycles	min. 4000000
	Motion velocity	max. 3 m/s
	Traverse distance	10 m
	Acceleration	max. 10 m/s ²
	Torsion cycles	min. 4000000
Tightening torque, cable gland	Torsional stress	± 270 °/m
		0.4 ... 0.6 Nm
Mating cycles		min. 100